



SITE SECURITY

Barb Wire - Crank Bar

SKU FA_BARBCR

A steel crank bar that mounts to the top of temporary fence panels to angle barbed wire outward, creating an overhang that prevents climbing and significantly increases perimeter security.

SPECIFICATION	DETAIL
Length	570mm
Weight	1.5kg
Tube Nominal Bore	40mm NB
Tube Outside Diameter	48mm
Wall Thickness	2.3mm
Strands Supported	Up to 4 strands of barbed wire

KEY FEATURES

- ✓ Angles barbed wire outward from the top of the fence panel
- ✓ Steel construction with durable corrosion-resistant finish
- ✓ Bolts securely to standard temporary fence panel uprights
- ✓ Compatible with standard barbed wire rolls
- ✓ Works alongside extension bars for additional height or projection

APPLICATIONS

Mining · Construction · Civil · Commercial & Industrial · Site Security

This document is a general guide only and does not constitute a quote. Product details are indicative and, while we do our best to keep our information current, they may change without notice and should be confirmed with us before ordering. Images are shown for illustration purposes only. This document is uncontrolled once downloaded or printed.

1800 137 233

rentafence.com.au · sales@rentafence.com.au

Rent A Fence Pty Ltd · ABN 19 396 900 781

Scan for the
live product page

